



● YOUR  
● SMART  
● ENERGY

# SMILE5

RESIDENTIAL SERIES

**CAPACITY** ▶

2.9 / 5.7 / 10.1 / 13.3 kWh  
expandable to 80.0 kWh



5kW single phase hybrid inverter

Fast response

UPS ability

24/7 Monitoring

- S elf sufficient
- M odular battery
- I ntelligent control
- L ong lifespan
- E ssential load protected
- 5 kW system

# SMILE5



Model		SMILE5			
<b>System Specification</b>					
<b>Nominal Output Power</b>		5000 W / 4600 W (DE)			
<b>Capacity Range</b>	2.9 ~ 17.2 kWh (96% DoD)	5.7 ~ 34.4 kWh (96% DoD)	10.1 ~ 60.6 kWh (96% DoD)	13.3 ~ 80.0 kWh (100% DoD)	
<b>Usable Capacity Range</b>	2.8 ~ 16.5 kWh	5.5 ~ 33.0 kWh	9.7 ~ 58.1 kWh	13.3 ~ 80.0 kWh	
<b>Battery Chemistry</b>		LFP (LiFePO4)			
<b>IP Protection</b>		IP21 (Indoor) / IP65 (Outdoor)			
<b>Warranty</b>		5 Year Product Warranty, 10 Year Battery Warranty			

<b>Inverter Technical Specification</b>			
<b>Model</b>	SMILE5-INV	<b>Rated Frequency</b>	50 / 60 Hz
<b>Max. PV Input Power</b>	2 x 3300 W	<b>Phase</b>	Single-Phase
<b>Max. PV Input Current</b>	2 x 12 A	<b>Backup</b>	UPS
<b>Max. PV Input Voltage</b>	580 V	<b>Display</b>	LCD
<b>MPPT Number</b>	2	<b>Communication</b>	Ethernet / WIFI
<b>MPPT Voltage Range</b>	125 ~ 550 V	<b>Start Up DC Voltage</b>	125 V
<b>Max. PV Short-circuit Current</b>	2 x 15 A	<b>Relative Humidity</b>	15% ~ 85% (No Condensing)
<b>Max. Charging/Discharging Current</b>	100 A	<b>Dimension (W x D x H)</b>	610 x 210 x 627 mm
<b>Max. Charging/Discharging Power</b>	5000 W	<b>Weight</b>	35 kg
<b>Rated Voltage</b>	230 V	<b>EMC</b>	EN 61000-6-1/2/3/4
<b>Safety</b>	IEC 62109-1&-2, IEC 62477-1, IEC 62040.1.1, IEC 62116		
<b>Grid Regulation</b>	VDE-AR-N 4105, VDE 0126-1-1, AS 4777.2/3, CEI 0-21, G99-1, G100, RD 1699, NRS 097-2-1, TOR Erzeuger Typ A		

<b>Battery Technical Specification</b>				
<b>Module Model</b>	M4856-P	SMILE5-BAT	SMILE-BAT-10.1P	SMILE-BAT-13.3P
<b>Module Capacity</b>	2.9 kWh	5.7 kWh	10.1 kWh	13.3 kWh
<b>Module Nominal Voltage</b>	51.2 V	51.2 V	48 V	48 V
<b>Operating Temperature Range</b>	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*
<b>Max. Modules in Parallel</b>	6	6	6	6**
<b>Max. Charging/Discharging Current</b>	56 A	56 A	100 A	100A
<b>Cycle Life</b>	10 000***	10 000***	8000***	8000***

\* When the temperature is below 0 °C or above 40 °C, the performance will be limited.

\*\* ≥2 needs to install expansion pack

\*\*\* Under specific test conditions



Headquarter: Alpha ESS Co., Ltd.  
 ☎ +86 513 8060 6891  
 ✉ info@alpha-ess.com  
 🌐 www.alpha-ess.com  
 📍 Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.  
 ☎ +86 512 6828 7609  
 ✉ info@alpha-ess.com  
 🌐 www.alpha-ess.com  
 📍 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

Australia: Alpha ESS Australia Pty. Ltd.  
 ☎ +61 402 500 520 (Sales)  
 +61 1300 968 933 (Technical Support)  
 ✉ australia@alpha-ess.com  
 🌐 www.alpha-ess.com.au  
 📍 Unit 1, 2 Ralph Street Alexandria NSW 2015

Germany: Alpha ESS Europe GmbH  
 ☎ +49 6103 4591 601  
 ✉ europe@alpha-ess.de  
 🌐 www.alpha-ess.de  
 📍 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Italy: Alpha ESS Italy S.r.l.  
 ☎ +39 599 239 50  
 ✉ info@alpha-ess.it  
 🌐 www.alpha-ess.it  
 📍 Via Loda, 17-41013 Castelfranco Emilia (MO)

Korea: Alpha ESS Korea Co., Ltd.  
 ☎ +82 64 721 2004  
 ✉ korea@alpha-ess.com  
 📍 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

UK: Alpha ESS UK Ltd.  
 ✉ uk@alpha-ess.com  
 📍 Drake House, Long Street, Dursley, gl11 4hh